



CONTACT

Erin Nied

Phone: 816.472.7974

E-mail: erin@robstan.com

FOR IMMEDIATE RELEASE

TREMCO INCORPORATED VALIDATES TWO LIQUID SEALANTS THROUGH SWR INSTITUTE'S VALIDATION PROGRAM

Tremco Incorporated, a major U.S. manufacturer of sealant and waterproofing products, recently submitted [Dymeric 240 Polyurethane Sealant](#) and [Dymonic Polyurethane Sealant](#) for validation to the Sealant, Waterproofing, & Restoration Institute (SWR Institute) Liquid Sealants Validation Program. The products passed when tested by third parties to verify that the products meet the ASTM tests identified below. By verifying that the data sheet for those tests are correct, end-users should feel confident about the product's stated capabilities.

The product was tested by DL Laboratories Inc. for conformance to ASTM C 719 and ASTM C 661. The following are the test results:

Dymeric 240 Polyurethane Sealant:

ASTM C 719: Adhesion and Cohesion of Elastomeric Joint Sealants Under Cyclic Movement [Hockman Cycle]; Pass: YES Extension: +50% Compression: -50%

Substrate: Unprimed and primed aluminum and mortar. [The aluminum substrate was primed with TREMprime Non Porous Primer and the mortar substrate was primed with Tremco Primer No.1].

ASTM C 661: Test Method for Indentation Hardness of Elastomeric - Type Sealants by Means of Durometer Hardness; Shore "A" Durometer Rating: 30.

Validation Date: 6/24/2008 – 6/23/2013

Dymonic Polyurethane Sealant

ASTM C 719: Adhesion and Cohesion of Elastomeric Joint Sealants Under Cyclic Movement [Hockman Cycle]; Pass: YES Extension: +25% Compression: -25%

Substrate: Unprimed and primed aluminum and mortar. [The aluminum substrate was primed with TREMprime Non Porous Primer and the mortar substrate was primed with Tremco Primer No.1].

ASTM C 661: Test Method for Indentation Hardness of Elastomeric - Type Sealants by Means of Durometer Hardness; Shore "A" Durometer Rating: 15.

Validation Date: 6/24/2008 – 6/23/2013

Manufacturers that wish to have their wall coating, deck coating, liquid sealant, or pre-cured sealant products validated through the respective programs simply choose an independent laboratory from a list provided by SWR Institute. Once the lab is chosen, the manufacturer provides the name of the product to be tested, as well as a current manufacturer data sheet with the stated performance characteristics, test results and any other collateral materials. The third-party lab will randomly purchase from a local retailer the product to be tested, and tests the product to the greatest claim on the manufacturer's data sheet.

For more information about the validation program or any other validated product, please contact SWR Institute Headquarters at 816.472.7974 or visit the SWR Institute Website at www.swrionline.org.

###